

Ribbed carpet

STANDARD PRODUCTION FLOOR COVERING

Red



9200 Red Carpet




9201 Dark red
0




9202 Bordeaux
0

1x50 meter
2x25 meter
2x50 meter
4x50 meter


Blue



9203 Light blue
0




9204 Blue



9205 Dark blue
0

2x25 meter
2x50 meter
4x50 meter

Brown




9206 Beige




9207 Brown-grey
0

2x25 meter
2x50 meter
4x50 meter


Green yellow




9208 Green




9209 Dark green
0



9210 Yellow



9211 Pink



9212 Orange

2x25 meter
2x50 meter
4x50 meter

White Grey Black



9213 White
0




9214 Light grey
0



9215 Grey
0




9216 Dark grey



9217 Black

2x25 meter
2x50 meter
4x50 meter

Ribbed carpet – flat backing or optional anti-slip foam backing upon request (note: foam backing voids the Class B fire rating); > 6,720 m²; standard production with protective film available
Recommended installation: Professional double-sided tape – 14-day residue-free removal 8090



9218

**Green artificial
grass
'Economic'
2x30meter**

9219

Recycled / New
Color subject to
market
availability
Width 2 meters –
various lengths



European tested Bfl-S1 (fl=Floor)

The European fire classification Contribution to fire

Euroclass	Fire tests	Room corner test	Contribution	In reality
Class A1	EN ISO1182=flammable EN ISO 1716=calorie value	No flame transshipment	No contribution	Not inflammable
Class A2	EN ISO 1182 or EN ISO1716 plus EN ISO 13823, Figa<120W/s +Thr<7,5MJ	No flame transshipment	Hardly a contribution	Practically not inflammable
Class B	EN ISO 13823, Figa<120W/s +Thr<7,5MJ EN ISO 11925-2 30sec-Fs<150mm-60sec	No flame transshipment	Very limited contribution	Very difficult inflammable
Class C	EN ISO 13823, Figa<250W/s +Thr<15MJ EN ISO 11925-2, Figa<250W/s 30sec-Fs<150mm-60sec	Flame transshipment 100KW after 10 min	High contribution	Inflammable
Class D	EN ISO 13823-2, Figa<750W/s EN ISO 11925-2 30sec-Fs<150mm-60sec	Flame transshipment 100KW after 2 min	High contribution	More inflammable
Class E	EN ISO 11925-2 15sec-Fs<150mm-20sec	Flame transshipment 100KW between 0- 2 min	Very high contribution	Very inflammable
Class F	Not tested or does not qualify for Class E	Unclassified	Undetermined	Extremely inflammable

Source : CE-publication

Smoke production

For the smoke production, there are three classes:

S1: Limited smoke production

S2: Average smoke production

S3: Huge smoke production